

LEGEND

EDGE OF GRAVEL **EXISTING** WATER PROBE EXISTING CULVERT EXISTING MAJOR CONTOURS EXISTING MINOR CONTOURS

DRAWING INDEX

DRAWING NUMBER	DESCRIPTION
D-1727-1000-01	OVERALL SITE PLAN, VICINITY MAP & DRAWING INDEX
D-1727-1000-02	EXISTING CONDITIONS PLAN
D-1727-1000-03	PROPOSED IMPLEMENTATION PLAN, SEQUENCE & NOTES
D-1727-1000-04	GRADING PLAN & LEGEND
D-1727-1000-05	PLANTING & COMMUNITY PLANS, SCHEDULE & LEGEND
D-1727-1000-06	HABITAT ENHANCEMENT PLAN & LEGEND
D-1727-1000-07	SECTIONS
D-1727-1000-08	SECTIONS
D-1727-1000-09	CHANNEL PROFILES
D-1727-1000-10	DETAILS & NOTES
D-1727-3000-01	EROSION AND SEDIMENT CONTROL COVER SHEET
D-1727-3000-02	CLEARING AND DEMOLITION ESC PLAN
D-1727-3000-03	GRADING/STREET/UTILITY CONSTRUCTION ESC PLAN
D-1727-3000-04	ESC DETAILS

3000 SERIES SHEETS SPECIFICALLY ADDRESS STATE OF OREGON DEQ 1200C PERMIT REQUIREMENTS

PROJECT TEAM

LOWER COLUMBIA ESTUARY PARTNERSHIP 811 SW NAITO PARKWAY, SUITE 410 PORTLAND, OR 97204 PHONE: (503) 915-0220 FAX: (503) 226-1580 CONTACT: BILL BENNETT, COORDINATOR bennett@lcrep.org

LOWER COLUMBIA RIVER WATERSHED COUNCIL PHONE: (503) 728-2945 CELL: (503) 709-9652
CONTACT: MARGARET MAGRUDER, COORDINATOR margruder@clatskanie.com

COLUMBIA SOIL & WATER CONSERVATION DISTRICT 35285 MILLARD ROAD ST. HELENS, OR 97051 PHONE: (503) 397-4555 CONTACT: TYLER JOKI

tyler.joki@or.nacdnet.net

amy_horstman@fws.gov

rick.stonex@gwrglobal.com

andrew@lowercolumbiaengr.com

U.S. FISH & WILDLIFE SERVICE 911 NE 11TH AVE #1 PORTLAND, OR 97232 PHONE: (503) 231-6121 CONTACT: AMÝ HORSTMAN

GREENWOOD RESOURCES, INC. 1500 SW 1ST AVE STE. 940 PORTLAND, OR 97201 PHONE: (971) 533-7065 CONTACT: RICK STONEX

LOWER COLUMBIA ENGINEERING 36200 PITTSBURG ROAD, SUITE E ST. HELENS, OR 97051 PHONE: (503) 366-0399 FAX: (503) 366-0449 CONTÀCT: ANDREW NIEMI, P.E.

KLS SURVEYING 1224 E. ALDER ST. VERNONIA, OR 97064 PHONE/FAX: (503) 429-6115 CONTACT: DON WALLACE, PLS dwallace@msn.com


UTILITY LOCATES

(48 HOUR NOTICE PRIOR TO EXCAVATION) OREGON LAW REQUIRES YOU TO FOLLOW THE RULES ADOPTED BY THE OREGON UTILITY NOTIFICATION CENTER. THOSE RULES ARE SET FORTH IN OAR 952-001-0010 THROUGH 952-001-0100. (YOU MAY OBTAIN COPIES OF THE RULES ROM THE CENTER BY CALLING 503 246 1987.) ONE CALL SYSTEM...... 1 800 332 2344

DATE: 12/19/12
ISSUED
FOR APPROVAL

St. Helens, Oreg (503) 366-0399

egon	PROJ. NO.	1727	COLUMBIA SOIL AND WATER CONSERVATION DIST.	•
	DWG. BY	TCO	LA SWAMP TIDAL RECONNECTION	
	APPR. BY		OVERALL SITE PLAN, VICINITY MAP, DRAWING IND)E
). 	SCALE N	OTED	DATE 12/04/12 DWG. NO. D-1727-1000-01	1



LOWER St. Helens, Oregon (503) 366-0399

Columbia

Engineering

St. Helens, Oregon (503) 366-0399

DWG. BY TCO LA SWAMP TIDAL RECONNECTION

APPR. BY

EXISTING CONDITIONS PLAN

DATE 12/04/12

DWG. NO. D-1727-1000-02

DATE: 12/19/12
ISSUED
FOR APPROVAL



REMOVAL/TREATMENT PLAN FOR NON-NATIVE INVASIVE SPECIES

THE AREA TO BE TREATED SHALL BE MOWED OR MECHANICALLY CUT TO THE GROUND PRECEDING HERBICIDE TREATMENT DURING MAY OR JUNE OF THE YEAR PRIOR TO IMPLEMENTATION.

2. ALLOW TO RESPROUT AND GROW TO APPROXIMATELY 18" TALL.

3. APPLY GARLON 3A HERBICIDE (OR EQUIVALENT APPROVED PRODUCT) PER MANUFACTURERS SPECIFICATIONS JUST PRIOR TO PLANTS DORMANT PERIOD DURING SEPTEMBER. MIXTURE SHALL BE 2.0% GARLON 3A AND .5% MODIFIED SEED OIL (MSO). WORK SHALL BE PERFORMED BY CERTIFIED APPLICATOR.

4. CONTRACTOR SHALL READ AND FOLLOW ALL PRODUCT LABELS AND APPLICATION INSTRUCTIONS FOR THE HERBICIDE USED.

5. LOWER COLUMBIA ENGINEERING IS NOT RESPONSIBLE FOR THE PROPER APPLICATION OF ANY HERBICIDAL PRODUCT.

6. DO NOT APPLY DIRECTLY TO FRESH WATER HABITATS.

7. TO AVOID RUN-OFF INTO ADJACENT STREAM DO NOT SPRAY BEFORE PERIODS OF HEAVY RAIN.

8. REPLANT NATIVE VEGETATION IN ORDER TO REOCCUPY THE AREA AS WELL AS TO PREVENT FURTHER INVASION BY HIMALAYAN BLACKBERRY OR OTHER INVASIVE SPECIES.

9. PERFORM SELECTIVE MAINTENANCE TREATMENTS IN ORDER TO REDUCE OR ELIMINATE COMPETING NON-NATIVE VEGETATION SURROUNDING NEWLY PLANTED NATIVE VEGETATION FOR A MINIMUM PERIOD OF FIVE YEARS. AVOID SPRAYING NATIVE PLANTS.

PROPOSED IMPLEMENTATION SEQUENCE

- INITIAL REMOVAL OF INVASIVE SPECIES SEE "REMOVAL/TREATEMENT PLAN FOR NON-NATIVE INVASIVE SPECIES" ABOVE.
- 2 PLUG ALL WATER ENTRY POINTS TO WORK AREA ON OR NEAR JULY 1ST.
- ANY ACCUMULATED WATER WITHIN WORK AREA SHALL BE PUMPED TO AN
- ESTABLISH STAGING AREA AND INSTALL INITIAL EROSION AND SEDIMENT
- INITIATE GRADING WORK WITHIN LEVEES PER PROPOSED GRADING PLAN ON SHEET 04. SCREEN AND DRY MATERIAL AS REQUIRED. DO NOT DISTURB EXISTING LEVEE AND BANK DURING ANY SITE ACTIVITIES UNTIL SPECIFIED. INSTALL ESC MEASURES, SEED AND STRAW MULCH
- INSTALL LARGE WOODY DEBRIS AND ASSOCIATED BALLAST ROCK INSIDE OF LEVEES PER HABITAT ENHANCEMENT PLAN ON SHEET 06.
- REMOVE EXISTING CULVERTS AND TIDE GATES AND EXCAVATE LEVEE BREACHES ALONG EXISTING LEVEES PER PROPOSED GRADING PLAN ON SHEET 04. CONSTRUCT TANDY CREEK CHANNEL MODIFICATIONS AT SE CORNER OF WORK AREA. PLACE AND COMPACT FILL AS PER SPECIFICATIONS ADJACENT TO BREACHES. INSTALL ESC MEASURES, SEED
- AND STRAW MULCH IMMEDIATELY AFTER COMPLETION OF EXCAVATION. PERFORM REMAINING GRADING ACTIVITY PER PROPOSED GRADING PLAN ON 8 SHEET 04. INSTALL ESC MEASURES, SEED AND STRAW MULCH
- INSTALL ANY REMAINING LARGE WOODY DEBRIS AND BALLAST ROCK AS PER HABITAT ENHANCEMENT PLAN ON SHEET 06.
- 10 INSTALL PLANTS PER PLANTING PLAN ON SHEET 05.
- 11 REMOVE ALL TEMPORARY SEDIMENT AND EROSION CONTROL FEATURES.
 - PERFORM NECESSARY OBSERVATIONS AND MAINTENANCE REQUIRED TO ENSURE PROJECT SUCCESS. AT A MINIMUM THIS SHALL INCLUDE THE FOLLOWING:

A. MANAGEMENT OF NON-NATIVE INVASIVE SPECIES PER REMOVAL/TREATMENT PLAN ABOVE. B. PROJECT AREA SHALL BE MONITORED FOR EROSION OR UNUSUAL

ACTIVITY AT A MINIMUM OF THREE TIMES PER YEAR FOR FIVE YEARS FOLLOWING IMPLEMENTATION. THIS SHALL INCLUDE CAREFUL OBSERVATION OF LEVEE BREACH AREAS FOLLOWING EXTREME TIDAL PERIODS. ANY EROSION OR UNUSUAL ACTIVITY SHALL BE BROUGHT TO THE ATTENTION OF LOWER COLUMBIA ENGINEERING. C. PLANTING SURVIVAL SHALL BE MONITORED ANNUALLY IN THE SPRING.

AREAS WITH UNACCEPTABLE LOSS SHALL BE REPLANTED BASED ON RECOMMENDATIONS BY BIOLOGIST.


DATE 12/04/12 DWG. NO. D-1727-1000-03


DATE: 12/19/12 ISSUED FOR APPROVAL


COLUMBIA ENGINEERING WITH ANY QUESTIONS OR UNCERTAINTIES PRIOR TO PROCEEDING.

REV.	REVISION RECORD	DATE	A Lower St. Helens, Oregon
			LOVV CI (503) 366-0399
			l 🛕 🎊 🛕 Columbia
			Engineering s
			Linginice in ig

_		
J	PROJ. NO. 1727	COLUMBIA SOIL AND WATER CONSERVATION DIST.
	DWG. BY TCO	LA SWAMP TIDAL RECONNECTION
	APPR. BY	IMPLEMENTATION PLAN, SEQUENCE & NOTES









					DATE: 12/19/12 ISSUED FOR APPROVAL
_	REVISION RECORD	DATE	A LOWer St. Helens, Oregon L	ROJ. NO. 1727	COLUMBIA SOIL AND WATER CONSERVATION DIST.
			A Columbia (303) 300-0399 DW	vg. by TCO	LA SWAMP TIDAL RECONNECTION
			Engineering	PPR. BY	HABITAT ENHANCEMENT PLAN & LEGEND
			SO SO	CALE NOTED	DATE 12/04/12 DWG. NO. D-1727-1000-06

NOTES:


- 1. THE LOGS SHALL BE INSTALLED IN NARROW TRENCHES, EXCAVATED JUST LARGE ENOUGH TO ACCEPT THE LOG OR PUSHED IN PLACE WITH ADJACENT NATIVE VEGETATION LEFT INTACT.
- 2. LOGS SHALL BE SKEWED TO THE CHANNEL, DO NOT INSTALL LOGS LEVEL.
- 3. BACKFILL TRENCH WITH NATIVE SOIL, IN ALL CASES, THE EXTENT OF BURIAL SHALL BE AS SHOWN (2/3 OF LENGTH MIN.). ADDITIONAL ANCHORING MAY BE NECESSARY AT LOCATIONS WITH ANTICIPATED SCOUR, AS DIRECTED ELSEWHERE ON THESE PLANS OR BY THE FIELD ENGINEER.
- 4. REVEGETATE AREA WITH WHOLE PLANTS OR SLIPS PER PLANTING PLAN.
- 5. TRENCHES MAY ROUTINELY BE IN EXCESS OF 4 FEET DEEP, NO PERSON SHALL BE ALLOWED NEAR OR IN ANY TRENCH AND THE TRENCH IS TO BE FILLED IMMEDIATELY AFTER EXCAVATION.
- 6. WATER IN THE TRENCH MAY FLOAT THE LOG. IN THESE CASES OTHER LOGS SHALL BE STACKED ON TOP OF THE LOG AND SUNK USING THE WEIGHT OF THE EXCAVATOR TO PUT THE LOG AT THE PROPER ELEVATION PRIOR TO BACKFILLING.



PLAN



TYPICAL LOG INSTALLATION DETAIL



GENERAL NOTES

4. A PUMP MUST BE ON HAND AT ALL TIMES FOR PUMPING SEEPAGE WATER AS NEEDED. IF

A PUMP IS USED FOR DIVERSION, A SECOND PUMP MUST BE ON SITE DURING CONSTRUCTION.

PROJECT AREA, CAPTURING ALL FISH AND RELEASING THEM UPSTREAM OF THE PROJECT AREA. WHILE THE PROJECT IS BEING DEWATERED, ODFW WILL ELECTROFISH THROUGH THE AREA TO CAPTURE ANY FISH THAT MAY HAVE ESCAPED THE FIRST PASS THROUGH AND RELEASE THEM

7. THE DOWN STREAM COFFER DAM SHALL NOT BE CONSTRUCTED UNTIL THE FULL FLOW IS RUNNING THROUGH THE DIVERSION, CONTRACTOR SHALL COORDINATE W/ ODFW FOR REMOVING

8. WHEN RE-WATERING ADD APPROXIMATELY 20% OF THE FLOW FOR 4 HOURS, THEN 50% FOR FOUR HOURS. PUMP SILTY WATER TO HIGHLAND PRIOR TO REMOVING LOWER COFFER DAM &

ANY FISH FROM WORK AREA AT LEAST ONE WEEK PRIOR TO COMPLETION OF DIVERSION.

6. PRIOR TO CONSTRUCTION A FISH BLOCK NET WITH $\frac{1}{4}$ INCH MESH WILL BE INSTALLED ABOVE THE PROJECT AREA. ODFW WILL WORK WITH THE CONTRACTOR TO ELECTROFISH THROUGH THE


. LOG PLACEMENT SHOWN IS ONLY CONCEPTUAL AND MAY BE ADJUSTED BASED ON DIRECTION BY FIELD ENGINEER.

5. FIELD ENGINEER SHALL APPROVE DIVERSION PIPE SIZE.

UPSTREAM OF THE PROJECT AREA.


RESTORING FULL FLOW.


- 2. NATIVE STREAMBED MATERIAL IN TANDY CREEK SHALL BE SALVAGED AND REUSED BEFORE ADDITIONAL GRAVEL IS INTRODUCED. ANY NECESSARY ADDITIONAL STREAMBED GRAVEL MIX SHALL BE EQUAL PARTS OF 7/8" DRAIN ROCK, 1 1/2" DRAIN ROCK AND 2" TO 6" COBBLE, ALL ROUNDED AND WASHED WITH NO FINE SEDIMENT. THIS BEDDING SHALL BE 8"-12" THICK AND EXTEND THROUGHOUT DISTURBED STREAMBED AREA AS REQUIRED.
- 3. ANY CASCADES SHALL NOT BE GREATER THAN 6" TALL FALLING INTO POOLS THAT FISH CAN JUMP FROM RATHER THAT SHALLOW SURFACES SUCH AS ROCKS.
- 4. WORK SHALL BE CONDUCTED ONLY DURING APPROVED WORK PERIOD BY ODFW. WORK PERIOD AND ANY REQUIRED EXTENSIONS MUST BE APPROVED BY ODFW PRIOR TO PERFORMING ANY WORK.
- 5. ALL AREAS BEHIND THE LEVEE BREACHES MUST BE WELL VEGETATED PRIOR TO THE BREACH TO PREVENT SEDIMENT FROM ENTERING THE RIVER FOLLOWING THE FIRST TIDAL
- 6. VEGETATION MATS AND SEED WILL BE INSTALLED IMMEDIATELY FOLLOWING THE LEVEE BREACHING ON ALL EXPOSED BARE SOILS.
- 7. CONTACT ENGINEER WITH ANY QUESTIONS OR UNCERTAINTIES REGARDING LOG PLACEMENT OR ANY OTHER ISSUES PRIOR TO PROCEEDING.
- 8. LOWER COLUMBIA ENGINEERING IS NOT RESPONSIBLE FOR ANY MOVEMENT OF LOGS OR BANK STABILIZATION ISSUES.




<u>NOTES</u>:

- 1. THE LOGS SHALL BE INSTALLED IN NARROW TRENCHES, EXCAVATED JUST LARGE ENOUGH TO ACCEPT THE LOG AND WITH ADJACENT VEGETATION LEFT INTACT.
- 2. LOGS SHALL BE SKEWED TO THE CHANNEL DO NOT INSTALL LOGS LEVEL.
- 3. BACKFILL TRENCH WITH NATIVE SOIL IN ALL CASES THE EXTENT OF BURIAL AS SHOWN ABOVE SHALL BE COMPLETED. ADDITIONAL ANCHORING MAY BE NECESSARY AT LOCATIONS WITH ANTICIPATED SCOUR. AS DIRECTED ELSEWHERE ON THESE PLANS OR BY THE FIELD ENGINEER.
- 4. REVEGETATE AREA WITH WHOLE PLANTS OR SLIPS PER PLANTING PLAN.
- 5. TRENCHES MAY ROUTINELY BE IN EXCESS OF 4 FEET DEEP, NO PERSON SHALL BE ALLOWED NEAR OR IN ANY TRENCH AND THE TRENCH IS TO BE FILLED IMMEDIATELY AFTER EXCAVATION.
- WATER IN THE TRENCH MAY FLOAT THE LOG. IN THESE CASES OTHER LOGS OR BALLAST ROCK SHALL BE STACKED ON TOP OF THE LOG AND SUNK USING THE WEIGHT OF THE EXCAVATOR TO PUT THE LOG AT THE PROPER ELEVATION PRIOR TO BACKFILLING.







TYPICAL LOG INSTALLATION DETAIL



- 1. SELECT LOCAL DOGWOOD, ELDERBERRY, WILLOW, TWIN BERRY, SALMONBERRY, NINEBARK, OCEANSPRAY, SNOWBERRY, CURRENT, HARDHACK, OR OTHER LOCAL SPECIES.
- 2. CLEANLY CUT INTO STAKES OF ANY SIZE FROM SMALLER THAN A PENCIL TO AS LARGE AS THE DONOR WILL ALLOW, SMALL STAKES ARE MUCH EASIER TO INSTALL, LARGE STAKES CAN STAND
- ABOVE COMPETING VEGETATION. EACH STAKE SHOULD HAVE AT LEAST 2 NODES (BUDS). 4. BUNDLE STAKES INTO MANAGEABLE GROUPS, RIGHTSIDE UP
- AND STORE IN THE STREAM UNTIL USE. 5. INSTALL BY SLIDING INTO GROUND AT A RANGE OF LOCATIONS, SOME HIGH AND SOME LOW WITH RESPECT TO ORDINARY HIGH
- WATER. 6. NEATLY TRIM ANY ENDS THAT ARE MASHED BY POUNDING. PERFORM FROM SEPTEMBER THRU MAY OR IN MOIST SOIL. 8. PLANTING DENSITY SHALL PROVIDE FOR MAXIMUM UNPLANTED AREA OF 2'-0" IN ANY DIRECTION.
- 9. INCLUDE LOCAL STAKE PLANTING AS DIRECTED BY PROJECT ADMINISTRATOR.







TYPICAL PLANTING DETAILS

NOTES:

1. SOAK BARE ROOT PLANTS FOR 24 HRS BEFORE PLANTING. 2. DIG HOLE APPROXIMATELY 2X ROOT BALL DIAMETER. 3. BACKFILL A CONE SHAPED MOUND IN THE HOLE. 4. SPREAD ROOTS EVENLY ON MOUND.

5. FILL ³/₄ FULL, COMPACT GENTLY AND ADJUST PLANT ALIGNMENT. 6. COMPLETE FILL AND CREATE RIDGE AROUND PLANT FOR A WATERING BASIN. 7. WATER THOROUGHLY. 8. STAKE AS NECESSARY.

1. DIG HOLE TWICE AS LARGE AS ROOT 2. BACKFILL A CONE SHAPED MOUND IN

THE HOLE. INSTALL TREE AND OPEN BURLAP TO FULLY EXPOSE SURFACE SOIL.

4. FILL \(\frac{3}{4}\) FULL, COMPACT GENTLY AND ADJUST PLANT ALIGNMENT. 5. COMPLETE FILL AND CREATE RIDGE AROUND PLANT FOR A WATERING BASIN. 6. STAKE AS NECESSARY.

7. WATER THOROUGHLY.

DATE: 12/19/12 ISSUED FOR APPROVAL

REV.	REVISION RECORD	DATE	St. Helens, Oregon PROJ. NO. 1727 COLUMBIA SOIL AND WATER CONSERVATION DIST.
			LOWER St. Helens, Oregon 1/2/ COLUMBIA SOIL AND WATER CONSERVATION DIST.
			LOWER St. Helens, Oregon (503) 366-0399 Columbia Columbia Mark Conservation dist. Dwg. by TCO LA SWAMP TIDAL RECONNECTION APPR. by DETAILS & NOTES
			Engineering DETAILS & NOTES SCALE DATE 1/2 DWG, NO. 1000
			SCALE NOTED DATE 40 /04 /40 DWG. NO. D. 4707 4000 40
			——————————————————————————————————————